

## Computer Code Abstracts

### CCA -112

1. Name of Code: AISITE II
2. Computer for Which Code is Designed and Others Upon Which it is Operable: IBM 7094
3. Nature of Physical Problem Solved: AISITE II is a code for the investigation of reactor-siting requirements and is largely based on methods proposed by the AEC in TID-14844 but differs in certain of the assumptions and models. The code automatically varies any one of 46 parameters such as reactor power, building leak rate, iodine cleanup rate, halogen filter efficiency, etc., and computes the exclusion area and low- and center-population-boundary zones as functions of that parameter. The edit includes dose-vs-distance data, fractional contribution by isotope group to the inhalation dose and critical distances and provides both printed and graphical data. Three models are available for fission product release with up to 4 levels of containment.
4. Method of Solution: Analytic solutions to the differential equations are evaluated.
5. Restrictions of the Complexity of the Problem:
  - 100 Isotopes
  - 20 Distances
  - 10 Values of variable parameter
  - 8 Organs
  - 4 Levels of containment
6. Typical Running Time: One case with 10 distances and 10 values of the variable parameter requires about 20 sec for both printed and graphical output.
7. Unusual Features of the Program: AISITE II has been optimized to reduce running time by keeping track of those portions of the calculation which need not be re-evaluated; i.e., are not affected by the variable parameter. This optimization resulted in up to a factor of 10 savings over the earlier version of the code.
8. Related and Auxiliary Programs: None
9. Status: In production
10. References:
  - <sup>1</sup>R. A. Blaine and E. L. Bramblett, "AISITE II, A Digital Computer Program for Investigation of Reactor Siting," NAA-SR-9982 (September 1964).
  - <sup>2</sup>M. Hoffman and W. A. Rhoades, "AICRT3, A General Code for Display of Digital Data," NAA-SR-MEMO-9069 (October 1963).
11. Machine Requirements:
  - 32k, IBM 7094
  - SC-4020 graphical display device
12. Programming Languages Used: FORTRAN II (90%) and FAP (10%)
13. Operating System or Monitor Under Which Program is Executed: Standard IBM FORTRAN Monitor.
14. Any Other Programming or Operating Information or Restrictions: If an SC-4020 graphical display device is not available, dummy routines can be used for sub-routines GRAPH and AICRT3, or these routines can be rewritten.
 

The NAA SC-4020 subroutine package is available through:

UAIDE Librarian  
c/o Stromberg-Carlson  
P. O. Box 2449  
San Diego, California
15. Material Available:
  - (a) Source deck (3000 cards)
  - (b) Sample case
  - (c) Documents
  - (d) Abstract

*R. A. Blaine*

Supervisor, Nuclear Codes Unit  
Mathematics and Computer Applications Group  
Atomics International  
P. O. Box 309  
Canoga Park, California

Received April 6, 1965

### CCA - 113

1. Name of Program: DPN-FIT
2. Computer for Which Program is Designed: IBM-709  
Programming Language: FORTRAN II with one tape unit.
3. Nature of the Problem Solved: The code performs a least-mean-squares fit of the analytic double  $P_N$  characteristic solutions to a set of measured scalar fluxes<sup>1</sup>. From the fitting coefficients the code reconstructs the angular flux that must be associated with the measured scalar fluxes. Then the code calculates the statistical uncertainty in the reconstructed angular flux caused by statistical uncertainty in the measured scalar fluxes.
4. Method of Solution: The fitting is done with the standard linear least-mean-squares technique and is implemented using simple matrix manipulations. The reconstruction process is reduced to a series of matrix operations as is the error analysis. The problem must be essentially spectrum independent.
5. Basic Physics Approximations: The spatial dependence of any sources present must be known in advance. A finite-order double  $P_N$  approximation must be able to represent the angular distribution (i.e., no delta functions in angle).